



DUMP INSERT
SPECIFICATION SHEET



DUMP INSERT



	6'6" STEEL DUMP INSERT	8' STEEL DUMP INSERT	6'6" ALUMINUM DUMP INSERT	8' ALUMINUM DUMP INSERT
Outside Length of Body	89.55	107.55	89.75	107.75
Inside Length of Body	85	103	85	103
Inside Width of Body (Floor)	48.5	48.5	48.75	48.75
Inside Width of Body (Upper)	61.53	61.53	61.5	61.5
Recommended CA	6'6" to 6'9" Pick Up bed length	8' Pick Up bed length	6'6" to 6'9" Pick Up bed length	8' Pick Up bed length
Headboard Height Options	Bolt on Option	Bolt on Option	Bolt on Option	Bolt on Option
Side Wall Height	21	21	21	21
Tailgate Height	21	21	21	21
Body Material	12ga Steel	12ga Steel	3/16" Aluminum	3/16" Aluminum
Subframe Material	2" x 1" Steel Tubing	2" x 1" Steel Tubing	2" x 1" Steel Tubing	2" x 1" Steel Tubing
Floor Material	12-GA 1010	12-GA 1010	3/16 5052	3/16 5052
Rear Lighting	Utilizes Trucks Existing Lighting	Utilizes Trucks Existing Lighting	Utilizes Trucks Existing Lighting	Utilizes Trucks Existing Lighting
Cylinder	Dual 32" Double Acting Cylinders	Dual 32" Double Acting Cylinders	Dual 32" Double Acting Cylinders	Dual 32" Double Acting Cylinders
Power Pack	Dual Acting 3,000 psi	Dual Acting 3,000 psi	Dual Acting 3,000 psi	Dual Acting 3,000 psi
Tarp System	Optional (Manual Crank)	Optional (Manual Crank)	Optional (Manual Crank)	Optional (Manual Crank)
Dump Angle	43	36	43	36
System Weight	740	820	520	600
Capacity Cu Yard (Struck)	2.02	2.45	2.02	2.45
Capacity Cu Yard (Heaping)	2.82	3.55	2.82	3.55