

FLAT DECK SPECIFICATION SHEET



FLAT DECK - NON-DUMPING



	12' STEEL FLATDECK	25' HITCH HIKER DECK	
Outside Length of Body	12'3"	25'8"	
Inside Deck Length	12'	25'	
Outside Deck Width	102" with Rub Rails with Pockets	102" with Rub Rails with Pockets	
Understructure	Cross Member	Cross Member	
Recommended CA	84" - 108" CA	219"	
Headboard Height Options	48" standard	74" Standard	
Subframe Length (Dumping or Longsill Length (Fixed)	11'	Fixed	
Headboard Height Options	(N/A) / 5"	(N/A) / 6"	
Headboard Material	10ga Smooth Steel with 3" Channel	10ga Smooth Steel with 4 x 2 x 3/16 Tubing	
Floor Material options	Wood	3/16" Checker Plate Steel	
Rear Lighting	5 Rear Markers, Chassis STT and reverse lights reused	5 Rear Markers, Chassis STT and reverse lights reused, 2 Mid Amber Marker Lights	
Cylinder Options	Fixed	Fixed	
Weight Range	1830	4750	
Dump Angle	Fixed	Fixed	



FLAT DECK - DUMPING



	16' STEEL DUMPING FLATDECK	16' ALUMINUM DUMPING FLATDECK	16' STEEL-GALVANIZED DUMPING FLATDECK
Outside Length of Body	16'8"	16'8"	16'8"
Inside Deck Length	16'	16'	16'
Dutside Deck Width	102" with Rub Rails with Pockets	102" with Rub Rails with Pockets	102" with Rub Rails with Pockets
Inderstructure	Cross Member	Cross Member	Cross Member
Recommended CA	120" - 132" CA	120" - 132" CA	120" - 132" CA
Headboard Height Options	48" standard	48" standard	48" Standard
Subframe Length (Dumping or Longsill Length (Fixed)	13'10"	13'10"	13'10"
leadboard Height Options	5" / 6"	5" / 6"	5" / 6"
leadboard Material	10ga Smooth Steel with 3" Channel	3/16" Smooth Aluminum with 3" Channel	10ga Smooth Steel with 3" Channel
loor Material options	10ga Smooth Steel	3/16" Checker Plate Aluminum	1-5/16" Apitong Wood
Rear Lighting	5 Rear Markers, Chassis STT and reverse lights reused, 2 Mid Amber Marker Lights	5 Rear Markers, Chassis STT and reverse lights reused, 2 Mid Amber Marker Lights	5 Rear Markers, Chassis STT and reverse lights reused, 2 Mid Amber Marker Lights
Cylinder Options	20 Ton Champion Scissor	20 Ton Champion Scissor	20 Ton Champion Scissor
Veight Range	3575	2190	3860
Jump Angle	45	45	45